

The `ifthen` package*

David Carlisle

2024/03/16

This file is maintained by the L^AT_EX Project team.
Bug reports can be opened (category `latex`) at
<https://latex-project.org/bugs.html>.

Abstract

This file implements an `\ifthenelse` command for L^AT_EX 2_ε. The algorithm used is compatible with that used in the L^AT_EX 2.09 `ifthen` style option. It has been recoded, making the resulting definitions somewhat more compact and efficient.

1 Introduction

`\ifthenelse` `\ifthenelse{<test>}{<then clause>}{<else clause>}`

Evaluates `<test>` as a boolean function, and then executes either `<then clause>` or `<else clause>`.

`<test>` is a boolean expression using the infix connectives, `\and`, `\or`, the unary `\not` and parentheses `\(\)`.

As an alternative notation `\AND`, `\OR` and `\NOT` can be used. This is safer since it can't be misinterpreted when appearing inside a T_EX-conditional in which `\or` has a different meaning.

The atomic propositions are:

`<number> < <number>`
`<number> = <number>`
`<number> > <number>`
`\isodd{ <number> }`
`\isundefined{ <command name> }`
`\equal{<string>}{<string>}`
`\lengthtest{<dimen>< <dimen>}`
`\lengthtest{<dimen>= <dimen>}`
`\lengthtest{<dimen>> <dimen>}`
`\boolean{<name>}`

The `<string>`s tested by `\equal` may be any sequence of commands that expand to a list of tokens. If these expansions are equal, then the proposition is true.

`\isodd` is true if the `<number>` is odd, and false otherwise (even if the argument is not a number).

*This file has version number v1.1e, last revised 2024/03/16.

`\isundefined{<cmd>}` is true if `<cmd>` is not defined.

`\boolean{xyz}` returns the truth value contained in the primitive T_EX `\if`, `\ifxyz`. This is usually used with boolean flags created with `\newboolean` and `\provideboolean` described below. It can also be used with the names of `\newif` created tokens, and primitive T_EX `\if` constructs, for example `\boolean{true}` (`\iftrue`), `\boolean{mmode}` (`\ifmmode`) etc.

The commands:

`\newboolean` `\newboolean{<name>}` and `\provideboolean{<name>}` are provided so the user
`\provideboolean` can easily create new boolean flags. As for `\newcommand`, `\newboolean` generates an error if the command name is not new. `\provideboolean` silently does nothing in that case.

The boolean flags may be set with:

`\setboolean` `\setboolean{<name>}{<value>}`
`<value>` may be either `true` or `false` (any CaSe).

Note that there is no precedence between `\and` and `\or`. The proposition is evaluated in a left right manner. `\not` only applies to the immediately following proposition. (This is consistent with Lamport's `ifthen.sty`.) In this style, though the test is 'lazily' evaluated, so for instance if the first proposition in an `\or` is true, the second one is skipped. (On the second pass—the first pass in an `\edef` expands clauses in all propositions.)

Apart from the addition of the extra atomic propositions `\isodd`, `\boolean`, `\lengthtest` and `\isundefined`, the only known incompatibility is that in this package the expression `\not\not<P>` is equivalent to `<P>`. However in the original style it was equivalent to `\not<P>`. This is intentional (bug fix:-).

`\whiledo` The command `\whiledo` is also defined (copied directly from the L^AT_EX2.09 definition).

`\whiledo{<test>}{<while clause>}`

With `<test>` as above, repeatedly executes `<while clause>` while the test remains true.

2 The Implementation

```
1 (*package)
```

`\TE@throw` In order to support the syntax of `ifthen.sty`, which allows access to the primitive T_EX syntax for a numeric test, rather than a `{}` delimited argument form, it is most convenient to work 'within' an `\ifnum`. `\ift@throw` 'throws' you out of the current `\ifnum` so that you can (eg) start an `\ifdim` for the length tests.

```
2 \def\TE@throw{\@ne=\@ne\noexpand\fi}
```

`\boolean` A non-standard extension to `ifthen`, supporting boolean was previously available, this is a simpler implementation.

```
3 \def\boolean#1#2{%
4 \TE@throw\expandafter\noexpand\csname if#1\endcsname#2}
```

`\TE@length` Testing lengths. `#1` is the test. The extra argument gobbles spaces.

```
5 \def\TE@length#1#2{\TE@throw\noexpand\ifdim#1#2}
```

`\TE@odd` Testing odd/even. This is true if `#1` is an odd number, and false otherwise (even `\TE@@odd` if `#1` is not a number at all).

It is hard to make this completely reliable. Here I have erred on the side of safety. This should not generate a T_EX error if given any robust commands as its argument. However it returns true on any argument that *starts* with an odd number 11xx which is bad, and it can not deal with T_EX's count registers, although L^AT_EX counters work (via \value).

```

6 \def\TE@odd#1#2{%
7 \TE@throw\noexpand\TE@@odd#1\noexpand\@nil\noexpand\ifodd\count@#2}
\TE@@odd is not expanded on the first pass.
8 \def\TE@@odd#1#2\@nil{%
9 \@defaultunits
10 \count@\if-#1-0\else0\expandafter#1\fi#2\relax\@nnil}

```

`\TE@repl` `\TE@repl` replaces the single token #1 by #2. (Not within {} groups.) It is used to replace `\or` by `\TE@or` without the need to redefine `\or`. Earlier versions just `\let\or\TE@or` but this has a bad effect on the expansion of commands which use the primitive `\or` internally, eg `\alph`, and so caused surprising results if these commands were used inside `\equal`.

```

11 \def\TE@repl#1#2{%
12 \long\def\@tempc##1#1##2{%
13 \def\@tempa{##2}\def\@tempb{\@tempc}%
14 \ifx\@tempa\@tempb
15 \toks@\expandafter{\the\toks@##1}%
16 \expandafter\@gobble
17 \else
18 \toks@\expandafter{\the\toks@##1#2}%
19 \expandafter\@tempc
20 \fi
21 ##2}%
22 \expandafter\toks@\expandafter{\expandafter}%
23 \expandafter\@tempc\the\toks@#1\@tempc}

```

`\ifthenelse` The remaining macros in this file are derived from the ones in `ifthen.sty` but recoded and simplified. The main simplification is that the original style (and the `\boolean` extensions) expressed logical values always in terms of `\ifnum`. As `\fi` is ‘untyped’ this is not necessary, so for example the length tests can return values via `\ifdim`, the trailing `\fi` will not complain, even though it was ‘expecting’ an `\ifnum`. Also the system of passing information via macros expanding to T or F has been completely replaced by a simpler system using `\iftrue`, which furthermore allows lazy evaluation on the second pass. With a LaTeX 2022/06/01 we have to ensure that `\pageref` is expandable.

```

24 \@ifl@t@r\fmtversion{2022/06/01}
25 {\def\TE@ref@exp{\let\pageref\@kernel@pageref@exp
26 \let\ref\@kernel@ref@exp}}
27 {\def\TE@ref@exp{\def\@setref##1##2##3{%
28 \ifx##1\relax\z@\else\expandafter##2##1\fi}}}
29 \begingroup
30 \lccode'\~'\> %
31 \catcode'\+\active
32 \lccode'\+ '\< %
33 \catcode'\!\active
34 \lccode'\! '\= %
35 \lowercase{\endgroup}

```

```

36 \def\TE@repl@active{%
37 \TE@repl~>%
38 \TE@repl+<%
39 \TE@repl!=%
40 }
41 \long\def\ifthenelse#1{%
42 \toks@{#1}%
43 \TE@repl\or\TE@or
44 \TE@repl\and\TE@and
45 \TE@repl\not\TE@neg
46 \TE@repl@active

```

Support alternate names for the boolean operators (strictly speaking only `\OR` would be necessary).

```

47 \TE@repl\OR\TE@or
48 \TE@repl\AND\TE@and
49 \TE@repl\NOT\TE@neg

```

The original `ifthen.sty` processed everything inside a box assignment, to catch any extra spaces before they appeared in the output. Instead I have added extra arguments to the commands so they each remove any following space.

Set up the user level names `\not` etc.

```

50 \begingroup
51 \let\protect\@unexpandable@protect
52 \TE@ref@exp
53 \def\value##1{\the\csname c@##1\endcsname}%
54 \let\equal\TE@equal \let\(\TE@lparen \let\)\TE@rparen
55 \let\isodd\TE@odd \let\lengthtest\TE@length
56 \let\isundefined\TE@undef

```

For the first pass, in a group, make various tokens non-expandable.

It is unfortunate that in order to remain compatible with `ifthen` syntax, it is necessary to have a two pass system. The first pass inside an `\edef` ‘exposes’ the `\if... \fi` tokens, so the correct clauses may be skipped on the second pass. This means that the whole `ifthenelse` command does not work by expansion, and so possibly has only limited usefulness for macro code writers. The main problem with the `ifthen:` syntax is that (unique for \LaTeX) it does not use a brace delimited argument form, and exposes the primitive \TeX syntax for $\langle number \rangle$. Pretty much the only way of parsing $1 > 2$ `\or` $2 < 1$ is to actually evaluate the primitive `\ifnums`. A syntax such as:

```
\or{\numtest{1<2}}{\lengthtest{1pt<1in}}
```

could easily be evaluated in a one pass way, operating directly via expansion, and leaving no extra tokens in the token stream.

Still, on with the code... make `\@tempa` and `\@tempb` tokens non-expandable on the first pass.

```

57 \begingroup
58 \let\@tempa\relax\let\@tempb\relax
59 \xdef\@gtempa{\expandafter\TE@eval\the\toks@\TE@endeval}%
60 \endgroup

```

Now outside the group, execute `\@gtempa` which causes all the `\ifs` etc., to be evaluated, the final truth value is contained in the `\newif` token `\ifTE@val`. Fi-

nally this is tested and either the first or second following argument is chosen accordingly.

```

61     \@gtempa
62     \expandafter\endgroup\ifTE@val
63     \expandafter\@firstoftwo
64     \else
65     \expandafter\@secondoftwo
66     \fi}%
67 }

```

`\TE@eval` Initialise a term. (Expanded on the first pass).

```
68 \def\TE@eval{\noexpand\TE@negatefalse\noexpand\iftrue\noexpand\ifnum}
```

`\ifTE@val` Two `\newifs` the first holds the current truth value of the expression. The second `\ifTE@negate` is a temporary flag which is true if we need to negate the current proposition.

```
69 \newif\ifTE@val
70 \newif\ifTE@negate

```

`\TE@endeval` Finalize a term. (Expanded on the first pass).

```

71 \def\TE@endeval{\relax
72     \noexpand\TE@setvaltrue\noexpand
73     \else
74     \noexpand\TE@setvalfalse\noexpand
75     \fi
76     \noexpand\TE@negatefalse\noexpand
77     \fi}

```

`\TE@setvaltrue` Set the `\ifTE@val` to true or false depending on the value of the current proposition, and the negate flag. (Not expanded on the first pass.)

```

78 \def\TE@setvaltrue{%
79     \ifTE@negate\TE@valfalse\else\TE@valtrue\fi}
80 \def\TE@setvalfalse{\let\ifTE@val\ifTE@negate}

```

`\TE@or` The internal version of `\or`. Ends the current term. If true skip the remaining terms.

```
81 \def\TE@or{\TE@endeval\noexpand\ifTE@val\noexpand\else\noexpand\ifnum}
```

`\TE@and` The internal version of `\and`. If false skip the remaining terms.

```
82 \def\TE@and{\TE@endeval\noexpand\ifTE@val\noexpand\ifnum}
```

`\TE@neg` `\not`. Throw the current context, set a negate flag, then restart the `\ifnum`.

`\TE@negswitch` `\TE@negswitch` is not expanded on the first pass.

```

83 \def\TE@neg{\TE@throw\noexpand\TE@negswitch\noexpand\ifnum}
84 \def\TE@negswitch{\ifTE@negate\TE@negatefalse\else\TE@negatetrue\fi}

```

`\TE@lparen` `\(`. Throw the current context, then restart a term inside a group.

```
85 \def\TE@lparen#1{\TE@throw\beginngroup\TE@eval#1}
```

`\TE@rparen` `\)` end the current term, and the local group started by `\(`, but pass on the boolean value in `\if\@val` T. The `\noexpand` stops the `\expandafter` from expanding on the first pass.

```

86 \def\TE@rparen#1{%
87     \TE@endeval
88     \noexpand\expandafter\endgroup\noexpand\ifTE@val#1}

```

`\TE@equal` `\equal` greatly simplified from the original. `\def` may be used rather than `\edef` as the whole thing is expanded anyway in the first pass. The boolean can be directly encoded with the `\ifx`, there is no need to start an equivalent `\ifnum`.

```
89 \long\def\TE@equal#1#2#3{\TE@throw
90   \def\@tempa{#1}\def\@tempb{#2}%
91   \noexpand\ifx\@tempa\@tempb#3}
```

`\setboolean` `\setboolean` takes true or false, as #2, and sets #1 accordingly.

```
92 \def\setboolean#1#2{%
93   \lowercase{\def\@tempa{#2}}%
94   \@ifundefined{@tempa\@tempa}%
95   {\PackageError{ifthen}%
96    {You can only set a boolean to ‘true’ or ‘false’}\@ehc}%
97   {\@ifundefined{#1\@tempa}%
98    {\PackageError{ifthen}{Boolean #1 undefined}\@ehc}%
99    {\csname#1\@tempa\endcsname}}}
```

`\newboolean` Define a new ‘boolean’.

```
100 \def\newboolean#1{%
101   \expandafter\ifdefinable\csname if#1\endcsname{%
102     \expandafter\newif\csname if#1\endcsname}}
```

`\provideboolean` Define a new ‘boolean’ if it is not already defined.

```
103 \def\provideboolean#1{%
104   \@ifundefined{if#1}{%
105     \expandafter\newif\csname if#1\endcsname}\relax}
```

`\whiledo` `\whiledo` copied directly from the original.
`\whiledo{<test>}{<body>}`
repeatedly evaluates `<body>` until `<test>` is true.

```
106 \long\def\whiledo#1#2{%
107   \ifthenelse{#1}%
108   {\@whiledottrue
109    \@whiles\if@whiledo\fi
110    {#2%
111     \ifthenelse{#1}\@whiledottrue\@whiledofalse}}%
112   {}%
113 }
```

`\TE@undef` test if csname is defined. `\ifx` test.

```
114 \def\TE@undef#1#2{%
115   \TE@throw\noexpand\ifx\noexpand\@undefined\noexpand#1#2}
```

`\if@whiledo` Internal switch for `\whiledo`.

```
116 \newif\if@whiledo
117 </package>
```