

Package ‘icecdr’

March 16, 2026

Type Package

Title Download Sea Ice Concentration Data from the NSIDC Climate Data Record

Version 1.0.0

Description Programmatic access to NSIDC's sea ice concentration CDR versions 4 and 5 via its ER-DAPP server. Supports caching results and optional fixes for some inconsistencies of the raw files.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.3.0)

RoxygenNote 7.3.3

Suggests here, ncdf4, rcd, testthat (>= 3.0.0), vcr

Imports checkmate, cli, digest, glue, httr2, rlang

URL <https://github.com/eliocamp/icecdr>

BugReports <https://github.com/eliocamp/icecdr/issues>

Config/testthat/edition 3

NeedsCompilation no

Author Elio Campitelli [cre, aut, cph] (ORCID:
<<https://orcid.org/0000-0002-7742-9230>>)

Maintainer Elio Campitelli <eliocampitelli@gmail.com>

Repository CRAN

Date/Publication 2026-03-16 16:20:09 UTC

Contents

cdr	2
cdr_antarctic_monthly	4
cdr_fix	6
Index	7

 cdr

Download sea ice concentration from NSIDC Climate Data Record

Description

This is a low-level function to download data from PolarWatch's ERDDAP server.

Usage

```

cdr(
  date_range = c(NA, NA),
  variables = "aice",
  hemisphere = c("south", "north"),
  resolution = c("monthly", "daily"),
  date_stride = 1,
  xgrid_range = c(NA, NA),
  xgrid_stride = 1,
  ygrid_range = c(NA, NA),
  ygrid_stride = 1,
  version = 5,
  format = "nc",
  file = NULL,
  dir = tempdir(),
  use_cache = FALSE
)

```

Arguments

date_range	<p>Vector of size two with the start and end dates. Supported formats are:</p> <ul style="list-style-type: none"> • A Date or POSIXct/POSIXlt object. • A character vector with ISO format dates: <code>c("2020-01-01", "2020-12-31")</code> • A character vector with year-month: <code>c("2020-01", "2020-06")</code> (expands to first/last day of month). • A character vector with year only: <code>c("2020", "2021")</code> (expands to full year).
variables	<p>Character vector with the variables to fetch. Valid values are</p> <p>aice CDR Sea ice concentration.</p> <p>qa Quality control flag.</p> <p>stdev Sea ice standard deviation.</p> <p>interpolation_spatial Flag for spatial interpolation.</p> <p>interpolation_temporal Flag for temporal interpolation.</p> <p>aice_bt Sea ice concentration of the Bootstrap method.</p> <p>aice_nt Sea ice concentration of the Nasa Team method.</p>

Although not all variables are available in all versions and all resolutions. The *_nt and *_bt variables are only available in version 4 and the interpolation flags are only available for daily values.

hemisphere	Character with the hemisphere to download. Can be either "south" or "north".
resolution	Character with the temporal resolution. Can be either "monthly" or "daily".
date_stride	Numeric with the temporal stride. A number greater than 1 means to take only the nth date in the series.
xgrid_range	Numeric vector of size 2 with the range of the x dimension.
xgrid_stride	Numeric with the stride of the x dimension.
ygrid_range	Numeric vector of size 2 with the range of the y dimension.
ygrid_stride	Numeric with the stride of the y dimension.
version	Version of the dataset. Can be 4 or 5.
format	Character with the format.
file	Character with the file name to use for download. If NULL, the file name will be constructed by hashing the request URL. Requests consisting in more than one file will append a number.
dir	Directory where to download the file.
use_cache	Logical indicating whether to not perform the download if the file already exist.

Value

Path or vector of paths to the downloaded files.

Examples

```
## Not run:
cdr(date_range = c("2022-01", "2022-01"),
    # Data every 7 days
    date_stride = 7,
    resolution = "daily",
    # Thin the grid by taking every other gridpoint
    xgrid_stride = 2,
    ygrid_stride = 2,
    hemisphere = "north"
)

## End(Not run)
```

cdr_antarctic_monthly Convenience functions

Description

These are convenience functions to download, daily or monthly sea ice concentration data from the whole Antarctic or Arctic. For a more complete low level function, see [cdr\(\)](#).

Usage

```
cdr_antarctic_monthly(  
  date_range,  
  variables = "aice",  
  version = 5,  
  file = NULL,  
  dir = tempdir(),  
  use_cache = FALSE  
)
```

```
cdr_antarctic_daily(  
  date_range,  
  variables = "aice",  
  version = 5,  
  file = NULL,  
  dir = tempdir(),  
  use_cache = FALSE  
)
```

```
cdr_arctic_monthly(  
  date_range,  
  variables = "aice",  
  version = 5,  
  file = NULL,  
  dir = tempdir(),  
  use_cache = FALSE  
)
```

```
cdr_arctic_daily(  
  date_range,  
  variables = "aice",  
  version = 5,  
  file = NULL,  
  dir = tempdir(),  
  use_cache = FALSE  
)
```

Arguments

date_range	<p>Vector of size two with the start and end dates. Supported formats are:</p> <ul style="list-style-type: none"> • A Date or POSIXct/POSIXlt object. • A character vector with ISO format dates: <code>c("2020-01-01", "2020-12-31")</code> • A character vector with year-month: <code>c("2020-01", "2020-06")</code> (expands to first/last day of month). • A character vector with year only: <code>c("2020", "2021")</code> (expands to full year).
variables	<p>Character vector with the variables to fetch. Valid values are</p> <p>aice CDR Sea ice concentration. qa Quality control flag. stdev Sea ice standard deviation. interpolation_spatial Flag for spatial interpolation. interpolation_temporal Flag for temporal interpolation. aice_bt Sea ice concentration of the Bootstrap method. aice_nt Sea ice concentration of the Nasa Team method.</p> <p>Although not all variables are available in all versions and all resolutions. The *_nt and *_bt variables are only available in version 4 and the interpolation flags are only available for daily values.</p>
version	Version of the dataset. Can be 4 or 5.
file	Character with the file name to use for download. If NULL, the file name will be constructed by hashing the request URL. Requests consisting in more than one file will append a number.
dir	Directory where to download the file.
use_cache	Logical indicating whether to not perform the download if the file already exist.

Value

A string vector with the location of the downloaded files

Examples

```
## Not run:
cdr_antarctic_monthly(c("2022-01", "2022-01"))

## End(Not run)
```

`cdr_fix`*Minor fixes to CDR files.*

Description

`cdr_fix()` "fixes" some inconsistencies in the raw data. It standardised variable names between versions and temporal resolutions and adds projection information to the grid definition so CDO can compute the area of each gridpoint to compute weighted means or area integrals. Both require the `rcdo` package and CDO installed.

Usage

```
cdr_fix(files, fix = c("names", "grid"))
```

```
cdr_fix_names(files)
```

```
cdr_fix_grid(files)
```

Arguments

`files` Path to the files.

`fix` Character vector with the fixes to implement.

Details

`cdr_fix_names()` and `cdr_fix_grid()` are aliases for `cdr_fix(fix = "names")` and `cdr_fix(fix = "grid")`, respectively. Using `cdr_fix()` to fix both at the same time is more efficient as it recreates each file only once.

Value

The path to the modified files.

Examples

```
## Not run:  
cdr_antarctic_monthly(c("2022-01", "2022-01")) |>  
  cdr_fix()  
  
## End(Not run)
```

Index

cdr, 2
cdr(), 4
cdr_antarctic_daily
 (cdr_antarctic_monthly), 4
cdr_antarctic_monthly, 4
cdr_arctic_daily
 (cdr_antarctic_monthly), 4
cdr_arctic_monthly
 (cdr_antarctic_monthly), 4
cdr_fix, 6
cdr_fix_grid (cdr_fix), 6
cdr_fix_names (cdr_fix), 6